








research challenge:


 How to sustain conjunctive use of the subsurface for on-site water supply and sanitation facilities?

research partners:










Trialling real-time monitoring of faecal contamination

- Tryptophan-Like Fluorescence (TLF) emitted by E. coli quantified using field fluorimeters
- evaluated against standard culture methods for TTCs and E. coli


=> Wed. AM session S05a (Sorensen et al.)





AfriWatSan observatories: faecal bacteria counts observed to rise in shallow wells after heavy rain events (> 10 mm/day)

- faecal particles trace rapid infiltration pathways (macropores)
- consistent with rapid responses observed from piezometry
 see this session S06 (Cisse Faye et al.)




AfriWatSan observatories: magnitude of faecal contamination not well explained WHO sanitary risk scores

AfriWatSan observatories: mapped on-site sanitation densities correlated to nitrate concentrations in groundwater

optical satellite imagery used, supported by ground surveys





=> see poster 312 today (Diaw et al.)

- provides empirical measure of an aquifer's ability to attenuate faecal loading using WHO nitrate guideline of 50 mg/L:
 - 7 pit latrines per ha (weathered crystalline rock Kisumu)
 - 24 septic tanks per ha (Quaternary sands Dakar)

Faecal contamination of shallow groundwater sources in slums of African cities is probable but not inevitable.



Summary:

- network of urban groundwater observatories
 established in a 'mega-city' (Dakar, Senegal), 'city'
 (Kisumu, Kenya) and 'town' (Lukaya, Uganda);
- 2. vulnerability of shallow groundwater revealed from faecal bacterial contamination following heavy rainfalls;
- 3. ability of shallow aquifers to attenuate faecal loading from on-site sanitation shown empirically;
- 4. knowledge of the groundwater "commons": a prerequisite for its sustainable use.



AFRIWATSAN PROJECT









